

General

Productgroup	PowerRadSok
Mounting type	Massive Pressfit Techn
Material	Brass
Surface	silver
Customs tariff number	85369095
Country of origin	Federal Republic of Germany
Weight per piecs ~	0.030580 kg

Technical data

Terminal / Type	Bolt / Diameter
Diameter x Length	8.000 mm x 31.50 mm

Socket length x Socket width	16.000 mm x 16.00 mm
Socket height	7.50 mm
Socket rounded	yes
Height total	42.50 mm
Height over pcb	39.00 mm
No. of Pins	36
Pin length	3.50 mm
Grid dimension X / Y	2.54 mm / 2.54 mm
Pin alignment	Full plain

Processing

Press in force	2160 N up to 9000 N
Retention force	60-80 % of press-in force
Press-in speed	100 mm/min. up to 250 mm/min.
PCB thickness	1.60 mm up to 3.20 mm
Notice	

Current carrying capacity

Part (20°C) ~ / (85°C) ~ 360.000 A / 216.000 A

Usage and storage

Temperature	-40 °C up to +150 °C
Storage	dry environment protected from weather conditions
Storage conditions	at +5 °C up to +40 °C, 75% RH, non-condensing


Accessories

Press in tool

Co-applicable documents

[Powerelement Guidelines](#) [Link to Powerelement Guidelines](#)

Standard drill pattern




Drill hole specification for PCB

Drill Ø		drill tool drill hole	1,60 mm 1,60 mm - 0,025 mm
Cu		Cu – in Hole	Average 30 µm – 60 µm min. 25 µm, max. 80 µm *
End Ø		HAL chem. surfaces	(1,450 mm +/- 0,05 mm) (1,475 mm +/- 0,05 mm)

Note: For Press-fit Technology drill diameter and copper thickness are fix. End Ø for reference only.

* single measurement points in microsection

Dimensions



**WÜRTH
ELEKTRONIK**
MORE THAN
YOU EXPECT

Würth Elektronik ICS GmbH & Co. KG
Würthstraße 1 74676 Niedernhall, Germany
P +49 7940 9810-4444 powerelement@we-online.de
www.powerelement.com

Observe protective note ISO 16016. Passing on or duplication without previous written agreement forbidden. Violations oblige to compensation. All rights reserved in the event of a patent or utility model protection. Subject to change without notice! Is NOT subject to change service!

Generaltolerances

DIN ISO 2768-mH

Projection mode



Revison

Date
17.09.25

All measures in
mm

Part no.

K94287

Description

PowerRadSok Bolt vertical



**REACH
COMPLIANT**



RoHS
COMPLIANT