General

Productgroup LF PowerOne

Massive Pressfit Techn Mounting type Material Brass lead-free (max. 0.1% Pb)

Surface tin

Customs tariff number 85369095

Country of origin Federal Republic of Germany

Weight per piecs ~ 0.010680 kg

Technical data

Terminal / Type Bush through hole / Metric 6.000 mm x 8.00 mm Thread/Diameter x Length

3.90 Nm Torque

Socket length x Socket width 13.000 mm x 13.00 mm

Socket height 8.00 mm Socket rounded ves Height total 11.50 mm 8.00 mm Height over pcb No. of Pins 16 Pin length 3.50 mm

2.54 mm / 2.54 mm Grid dimension X / Y Pin alignment Circumference with hole

Processing

PCB thickness

Press in force 960 N up to 4000 N 60-80 % of press-in force Retention force Press-in speed 100 mm/min, up to 250 mm/min.

Notice

Current carrying capacity

Part (20°C) ~ / (85°C) ~ 240.000 A / 144.000 A

Usage and storage

Temperature -40°C up to +150°C

dry environment protected from weather Storage

conditions

Storage conditions at +5°C up to +40°C, 75% RH,

non-condensing

1.60 mm up to 3.20 mm


Accessories

Press in tool

Co-applicable documents

Link to Powerelement Guidelines Powerelement Guidelines

Standard drill pattern




Drill hole specification for PCB


Drill Ø	drill tool drill hole	1,60 mm 1,60 mm - 0,025 mm
Cu-H	Cu – in Hole	Average 30 μm – 60 μm min. 25 μm, max. 80 μm *
End Ø	HAL chem. surfaces	(1,450 mm +/- 0,05 mm) (1,475 mm +/- 0,05 mm)
Note: For Press-fit Technology drill diameter and copper		


thickness are fix. End Ø for reference only.

* single measurement points in microsection

Dimensions











Α



Würth Elektronik ICS GmbH & Co. KG Würthstraße 1 74676 Niedernhall, Germany P +49 7940 9810-4444 lf-powerelement@we-online.de www.lf-powerelements.com

Observe protective note ISO 16016. Passing on or duplication without previous written agreement forbidden. Violations oblige to compensation. All rights reserved in the event of a patent or utility model protection. Subject to change without notice! Is NOT subject to change service!

Generaltolerances	1	Projection mode
DIN ISO 2768-mH		□ •
Revison	Date	All measures in

mm

28.07.25

Part no.

LF991106

Description

LF PowerOne Bush vertical through hole

